

Package: shinyComponents (via r-universe)

August 10, 2024

Title 'Shiny' Components in 'R Markdown'

Version 0.0.1.9000

Description 'Shiny' components, stored in 'R Markdown' documents.

License MIT + file LICENSE

URL <https://github.com/gadenbuie/shinyComponents>

BugReports <https://github.com/gadenbuie/shinyComponents/issues>

Imports htmltools, knitr, R6, rlang, sass, shiny, yaml

Suggests rmarkdown

Encoding UTF-8

LazyData true

Roxygen list(markdown = TRUE)

RoxygenNote 7.1.1

Repository <https://gadenbuie.r-universe.dev>

RemoteUrl <https://github.com/gadenbuie/shinyComponents>

RemoteRef main

RemoteSha 2ffb51244d01faef370a0a81c7c316be82235597

Contents

ShinyComponent	2
Index	3

Description

Shiny Components are self-contained shiny modules or app components, defined in R Markdown documents.

Public fields

ui The UI components. If the component contains only one unnamed ui chunk, or one ui chunk named ui, then this field is a method, otherwise it is a list of ui component methods.

server The server components. If the component contains only one unnamed server chunk, or one server chunk named server, then this field is a method, otherwise it is a list of server component methods.

dependencies A list of the component's HTML dependencies.

Methods**Public methods:**

- [ShinyComponent\\$new\(\)](#)
- [ShinyComponent\\$assets\(\)](#)
- [ShinyComponent\\$app\(\)](#)

Method `new()`: Initialize the Shiny Component from an R Markdown file.

Usage:

`ShinyComponent$new(file)`

Arguments:

`file` Path to the R Markdown document

Returns: A new Shiny Component

Method `assets()`: The component's CSS, compiled SASS, and JavaScript assets.

Usage:

`ShinyComponent$assets()`

Returns: A [shiny::tagList\(\)](#) containing the component's CSS and JavaScript assets.

Method `app()`: An example app, created from the primary ui and server.

Usage:

`ShinyComponent$app(..., id = NULL, .ui = list(), .server = list())`

Arguments:

`...` Additional variables added into ui and server environments, in ui, server and app methods. Otherwise, ignored.

`id` The component ID, if the component is being used as Shiny module.

`.ui` A list of arguments to be passed on to the `ui()` method.

`.server` A list of arguments to be passed on to the `server()` method.

Index

`shiny::tagList()`, [2](#)
`ShinyComponent`, [2](#)